

Butcher Boy  
Machines  
International LLC



flU 66  
FEED GRINDER



**MADE** *in* **USA**

640 Mulberry Avenue  
Selmer, Tennessee 38375

[www.butcherboymachines.com](http://www.butcherboymachines.com)

731-434-1012

800-237-5806

# SPECIFICATIONS

## Motor:

- 40 HP, 208/230/460 VAC, 3 Phase, 60 hertz.
- Motor conforms to NEMA specifications.
- Other motor configurations available.
- Specify power requirements with order.

## Motor Controls:

- All machines come with motor controls as standard equipment.
- Overcurrent protection must be supplied by user at time of installation.

## Process Control:

- Achieved by switches located on or within the AU66

## Production Capacity:

- 66 grinder (8 5/8" diameter plate) may grind +/- 18,000 pounds per hour (depending on plate hole size) when continuously fed.

## Construction:

- All surface areas and product contact areas are made from 18-8 stainless steel.

## Safety Features:

- Lockout switch:
  - Lockout/tag out incoming power.
- Safety Switch at tub grid cover:
  - will not allow operation unless properly closed.
- Feed box cover switch:
  - will not allow operation unless properly closed.
- Control Voltage 24 VAC

## Variable Height:

- Legs have a 12" adjustability to allow for a 28" to 40" clearance under the grinder.

## Cleaning Features:

- The only tool required to disassemble for cleaning is the wrench for the Knife & Plate Ring.

## Standard Equipment:

- Spurt guard
- Spanner wrench
- Operation, maintenance and parts manual

## Plate Size:

- 8 5/8" barrel, 8 5/8" plate (size 66 plate).

## Weight

- Shipping 1920 lbs.

# DIMENSIONS

