





MADEUSA

640 Mulberry Avenue Selmer, Tennessee 38375 www.butcherboymachines.com 731-434-1012 800-237-5806

# **SPECIFICATIONS**

#### Motor:

- ■2 HP or 3HP, 208/230/460 VAC. 3 phase, 60 Hz.
- ■2 HP or 3 HP 208/230 VAC. 1 phase, 60 Hz.
- Other motor configurations available.
- Motor conforms to NEMA specifications.
- Specify power requirements with order.

#### **Motor Controls:**

- All machines come with motor controls as standard equipment.
- Overcurrent protection must be supplied by user at time of installation.

### **Cleaning Features:**

Pan and cutting group are easily removed without the use of tools for cleaning.

### **Process Control:**

Achieved by on/off switch located on the TCA 32 and rate of hand feed.

#### Construction:

- All surface areas and product contact areas are made from 18-8 stainless steel.
- The pan guard and ring are aluminum.
- The cutting group is hot tin dipped.

### **Safety Features:**

- Pan Guard
- Control Voltage 24 VAC

#### **Standard Equipment:**

- Stomper: Which must be used to push product into grinder.
- Operation, maintenance, and parts manual.

#### **Production Capacity:**

■ 32 grinder (3 1 1 4 6 diameter
Cleveland style plate)
may grind +/- 40-50 pounds
per minute (depending
on plate hole size) when
continuously fed.

## Weight:

- Net 180 lbs.
- Shipping 210 lbs.

## DIMENSIONS

